



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B41J 2/175	A1	(11) International Publication Number: WO 00/68018 (43) International Publication Date: 16 November 2000 (16.11.00)
(21) International Application Number: PCT/GB00/01718 (22) International Filing Date: 5 May 2000 (05.05.00) (30) Priority Data: 9910313.7 5 May 1999 (05.05.99) GB (71) Applicant (for all designated States except US): CAMBRIDGE CONSULTANTS LIMITED [GB/GB]; Science Park, Milton Road, Cambridge CB4 0DW (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): VOSAHLO, Jindrich [GB/GB]; Smithy Cottage, Abington Pigotts, Royston, Cambridgeshire SG8 0SD (GB). (74) Agents: SIMONS, Elisabeth, Anne et al.; Mathys & Squire, 100 Gray's Inn Road, London WC1X 8AL (GB).		(81) Designated States: GB, IL, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: FLUID-PRESSURE CONTROLLED INK PRESSURE REGULATOR <div data-bbox="505 1087 1242 1669" data-label="Diagram"> </div>		
(57) Abstract <p>A pressure regulation system for an inkjet printer comprises a chamber (2) for containing ink, level sensing means (4) for measuring the level of ink contained in the chamber (2), a pressure source (3) for providing a fluid at a controlled positive or negative gauge pressure, and a pressure control means for controlling the pressure source. An ink supply regulating means (6) regulates the flow of ink and an ink flow control means (5) controls the ink supply regulating means (6) based on an output of the level sensing means (4). The pressure regulation system can be mounted close to the printhead (1).</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Larvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

FLUID-PRESSURE CONTROLLED INK PRESSURE REGULATOR

5 The invention relates to an ink pressure regulator. The invention finds particular but not exclusive application for use with inkjet printers. Embodiments of the present invention relate to a vacuum-controlled ink pressure regulator for ink supplied to a drop on demand inkjet printhead. Embodiments of the present invention relates to a vacuum controlled ink pressure regulator for use with a printer using a bulk ink supply.

10

One known technique for regulating the pressure of ink fed to an inkjet printhead is to control the pressure in an ink reservoir which is placed close to or integrated into the printhead. However, this technique is unsuitable for applications with high ink usage and/or long autonomy requirements, where the ink reservoir needs to be large and it is impractical to mount the reservoir in close proximity to a printhead.

15

For systems which use ink reservoirs which are mounted remotely from the printheads they supply, a known technique for regulating the pressure of ink fed to the printhead is to regulate the ink pressure remotely from the printhead (for example at the reservoir) and connect the pressure regulator to the printhead via a long ink tube. This technique has the disadvantage of there being pressure fluctuations at the printhead due to flow-dependent hydraulic losses in the long ink tube, movement of the long ink tube or from air within the tube. Such fluctuations impair printhead performance.

25

Prior art pressure regulators generally use either the height of ink to control pressure (level control) or a spring, or capillary action. Examples of level control pressure regulators include Trident International's printing systems for industrial coding applications and Hewlett-Packard's off-axis 'flaccid bag' (see EP-A-0 903 238). An example of a mechanical pressure regulator using a spring mechanism is shown in US 5,844,577. An example of a pressure regulator using capillary action is shown in US 5,745,138.

30

A common method of providing a constant gauge pressure at the printhead is to

- 2 -

expose part of the ink system to atmospheric pressure, and control the height difference between this exposed part and the printhead. Since some drop on demand printheads require a negative gauge pressure, to provide such a negative pressure using this method, the exposed part of the ink system must be below the printhead.

5 In applications where a print substrate is below the printhead, this exposed part of the ink system must also be below the level of the print substrate. This is very inconvenient and often requires a long ink tube between the printhead and the exposed part in order to find a suitable space.

10 Whilst it would be desirable to have a pressure regulator close to or at the printhead, when using a remote ink reservoir, prior art pressure regulators are generally not such that they could be simply mounted at or near the printhead. This is particularly the case when the pressure of the ink needs to be regulated to be negative at the printhead.

15

It is an object of embodiments of the present invention to provide a pressure regulation system for an inkjet printer which allows the pressure of the ink to be regulated at or near to the printhead whilst using a remote reservoir.

20 An aspect of the present invention provides a pressure regulation system for an inkjet printer comprising a chamber for containing ink, level sensing means for measuring the level of ink contained in the chamber, a pressure source for providing a fluid at a controlled positive or negative gauge pressure, a pressure control means for controlling the pressure source, an ink supply regulating means for regulating the
25 flow of ink and an ink flow control means for controlling the ink supply regulating means based on an output of the level sensing means.

In a preferred embodiment, a flexible barrier is positioned within the chamber and the level sensing means comprises a position sensing means which senses the position of
30 the flexible barrier.

Embodiments of the present invention overcome the problems mentioned above by allowing all the components of an ink supply system to be above the level of the printhead, even when a negative gauge pressure is required at the printhead.

- 3 -

Examples of pressure regulation systems according to the present invention allow regulation of the ink pressure to be carried out close to a printhead through using a fluid (preferably a gas) at a controlled pressure to control the pressure of the ink.

- 5 The present invention allows pressure regulation very close to the printhead with a small fluid volume, this is particularly useful for systems where the printheads move, but is also useful for fixed head systems. The chamber of the present invention may be mounted above the nozzle line and still provide negative pressure at the printhead. Air bubbles can rise to the float chamber where they do not cause trouble.

10

The present invention allows the ink supply pressure to be varied to suit current conditions or for maintenance routines if this is required.

- 15 In many cases, a negative pressure in the ink chamber is required, and in such cases the pressure source preferably comprises a vacuum source.

While the use of other fluids is contemplated, preferably the fluid is a gas, preferably air.

- 20 In embodiments of the invention, the ink supply means preferably comprises a pump. That pump can be used to assist in the efficient transfer of ink from an ink reservoir to the ink chamber.

- 25 Preferably the system further includes means for deactivating the ink supply means if the level in the chamber rises above a predetermined value. This provides a safety cut-out which stops ink flowing into the ink chamber if the level rises above a particular value.

- 30 Preferably the chamber is adapted to be mounted above a printhead. And preferably the system is adapted to be mounted above a printhead.

The invention further provides an ink delivery system for an inkjet printer comprising:

an ink chamber arranged for receiving ink from a reservoir;

an ink supply device for transferring ink from the reservoir to the ink chamber;
a control device for controlling the ink supply device; and
a sensor for determining the level of ink in the ink chamber and sending an
5 output to the control device;
wherein the control device is adapted to control the ink supply device based on the
output from the sensor.

Preferably the ink delivery system further includes a pressure source for applying a
10 pressure to the ink chamber.

The invention also provides a control device for an ink delivery system, the control
device comprising:

an input for receiving a signal from the sensor representative of the level of
15 ink in the ink chamber; and
an output for sending a signal to the ink supply device,
wherein the control device is programmed to send a signal to the ink supply device
when the signal from the sensor indicates that the ink in the ink chamber is at a
predetermined level. The control device may include a suitably programmed
20 processor.

A further aspect of the invention provides a pressure regulation system for an inkjet
printer comprising:

an ink chamber arranged for receiving ink from a reservoir; and
25 a pressure source for applying a pressure to the ink chamber.

Also provided by the invention is an inkjet printer comprising an ink delivery system,
a control device or a pressure regulation system as described herein.

30 The invention further provides a method of regulating pressure in an inkjet printer
comprising:

applying a pressure to an ink chamber;
determining the level of ink in the ink chamber; and
activating an ink supply device to supply ink to the ink chamber when the

- 5 -

level is at a predetermined value.

The invention also provides a computer program and a computer program product for carrying out any of the methods described herein, and a computer readable medium
5 having stored thereon a program for carrying out any of the methods described herein.

The invention also provides a method substantially as described herein with reference to the accompanying drawings, and apparatus substantially as described herein with
10 reference to and as illustrated in the accompanying drawings.

Apparatus features may be applied to the method features and vice versa. Features of one aspect of the invention may be applied to features of another aspect of the invention.

15

Further aspects, advantages and objectives of the invention will become apparent from a consideration of the drawings and the ensuing description, which, by way of example, describe embodiments of the present invention in which the pressure source is a vacuum source and a solenoid-driven on-off valve is used as the ink supply
20 regulating means.

Embodiments of the invention will now be described, by way of example, having reference to the drawings, of which:

25 Figure 1: Schematic diagram of an ink pressure regulator arrangement.

 Figure 2: Schematic diagram of an example of a level sensing means.

Figure 1 shows a printhead (1) which is fed with ink (8) from a chamber (2). A level
30 sensor (4) within the chamber measures the level of ink within the chamber and outputs a signal to an ink flow controller (5) which controls a solenoid-driven on-off ink supply valve (6). Ink is supplied to the chamber (2) from an ink reservoir (7). A controllable vacuum source (3) is used to control the pressure of the space above the ink in the chamber (2).

The pressure of the ink being supplied to the printhead (1) depends on the height of the chamber (2) above the printhead (1) and the gauge pressure of the controlled vacuum source (3) applied to the top of the chamber (2).

- 5 A level sensor (4) is used to enable the ink flow controller (5) to maintain the ink level using the ink supply valve (6). When the level is low, the ink flow controller (5) opens the ink supply valve (6) allowing ink to flow from the ink reservoir (7) into the chamber (2). Opening and shutting the ink supply valve (6) does not affect the pressure of ink supplied to the printhead because of the free surface in the float
10 chamber.

Bubbles within the ink (8) in the tubing between the chamber (2) and the printhead (1) will tend to rise into the chamber (1) where they are harmless.

- 15 The level sensor (4) may be a float switch, an optical device, an ultrasonic device, or any other suitable level sensing device.

The controlled vacuum can be, for example, generated using a vacuum pump, a solenoid valve, a vacuum reservoir and an accurate pressure sensor. A single
20 controlled vacuum source can be used to control multiple printheads with multiple chambers.

The printhead (1) can be flushed through with ink for maintenance by varying the controlled vacuum. This can be done by switching the chamber between the
25 controlled vacuum supply and ambient pressure, in this way a single head can be flushed while a single controlled vacuum is supplying many heads.

In order to cause the ink to flow through the supply valve to the printhead, the supply reservoir (6) may be pressurised. Alternatively, since some printheads act as pumps
30 and so can "suck" in the ink, the supply reservoir may be at ambient (or even negative) pressure. Other means of causing the ink to flow are also known to the person skilled in the art.

An electromechanical pump can be used in conjunction with a non-return valve as an

alternative to the solenoid-driven ink supply valve.

Care is needed to make sure that the ink level cannot accidentally get so high that ink enters the vacuum system. This can be achieved by having a second "safety" level sensor to cut off the ink supply (not shown), and/or by monitoring the ink supply 'on'-time and shutting down if apparent ink consumption is excessive.

The chamber (2) can be realised as a plenum chamber (Figure 2) where the ink is sealed from the gas by a thin flexible barrier (9). This prevents air diffusing into the ink, and also prevents volatile components of the ink being lost. It also prevents ink entering the vacuum system (3). In this case, a position sensor (10) sensing the position of the flexible barrier (9) is used as the level sensor.

Even when a negative pressure is required at the printhead, the chamber (2) can be positioned above the printhead, since the negative pressure is provided by the vacuum source. It is most convenient to be able to locate all components of an ink supply system above the level of a printhead when printing downwards.

It will be understood that the present invention has been described above purely by way of example and modifications of detail can be made within the scope of the invention.

Each feature disclosed in the description, and (where appropriate) the claims and drawings may be provided independently or in any appropriate combination.

25

Claims:

1. A pressure regulation system for an inkjet printer comprising a chamber for
5 containing ink, level sensing means for measuring the level of ink contained
in the chamber, a pressure source for providing a fluid at a controlled positive
or negative gauge pressure, a pressure control means for controlling the
pressure source, an ink supply regulating means for regulating the flow of ink
and an ink flow control means for controlling the ink supply regulating means
10 based on an output of the level sensing means.
2. A pressure regulation system according to claim 1 in which a flexible barrier
is positioned within the chamber and the level sensing means comprises a
position sensing means which senses the position of the flexible barrier.
- 15 3. A pressure regulation system according to any of the preceding claims where
the ink supply means is a solenoid operated valve.
4. A pressure regulation system according to any one of claims 1 to 3, wherein
20 the pressure source comprises a vacuum source.
5. A pressure regulation system according to any one of claims 1 to 4, wherein
the fluid is a gas.
- 25 6. A pressure regulation system according to any one of claims 1 to 5, wherein
the ink supply means comprises a pump.
7. A pressure regulation system according to any one of claims 1 to 6, further
including means for deactivating the ink supply means if the level in the
30 chamber rises above a predetermined value.
8. A pressure regulation system according to any one of claims 1 to 7, wherein
the chamber is adapted to be mounted above a printhead.

- 9 -

9. A pressure regulation system according to any one of claims 1 to 8, wherein the system is adapted to be mounted above a printhead.
10. An inkjet printhead which comprises a pressure regulation system according to any of the preceding claims.
11. An ink delivery system for an inkjet printer comprising:
an ink chamber arranged for receiving ink from a reservoir;
an ink supply device for transferring ink from the reservoir to the ink chamber;
a control device for controlling the ink supply device; and
a sensor for determining the level of ink in the ink chamber and sending an output to the control device;
wherein the control device is adapted to control the ink supply device based on the output from the sensor.
12. An ink delivery system according to claim 11, further including a pressure source for applying a positive or negative gauge pressure to the ink chamber.
13. A control device for an ink delivery system according to claim 10 or claim 11, comprising:
an input for receiving a signal from the sensor representative of the level of ink in the ink chamber; and
an output for sending a signal to the ink supply device,
wherein the control device is programmed to send a signal to the ink supply device when the signal from the sensor indicates that the ink in the ink chamber is at a predetermined level.
14. A pressure regulation system for an inkjet printer comprising:
an ink chamber arranged for receiving ink from a reservoir; and
a pressure source for applying a pressure to the ink chamber.
15. An inkjet printer comprising an ink delivery system according to claim 11 or claim 12, a control device according to claim 13 or a pressure regulation

- 10 -

system according to any one of claims 1 to 9 or claim 14.

16. A method of regulating pressure in an inkjet printer comprising:
- applying a pressure to an ink chamber;
 - 5 determining the level of ink in the ink chamber; and
 - activating an ink supply device to supply ink to the ink chamber when the level is at a predetermined value.

10

Figure 1





Figure 2



INTERNATIONAL SEARCH REPORT

Int. Application No.
PCT/GB 00/01718

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B41J2/175

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B41J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 838 339 A (HEWLETT PACKARD CO) 29 April 1998 (1998-04-29) column 3, line 29 -column 5, line 23 column 7, line 32 -column 9, line 6 figures 1,8-10	11,13
A		1-3, 7-10, 14-16
X	US 5 880 748 A (CHILDERS WINTHROP D ET AL) 9 March 1999 (1999-03-09) column 4, line 62 -column 5, line 68 column 6, line 10 -column 7, line 67 figures 2,3,5-8	11,13
A		1-3,7,15
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- * "A" document defining the general state of the art which is not considered to be of particular relevance
- * "E" earlier document but published on or after the international filing date
- * "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- * "O" document referring to an oral disclosure, use, exhibition or other means
- * "P" document published prior to the international filing date but later than the priority date claimed

* "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

* "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

* "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

* "8" document member of the same patent family

Date of the actual completion of the international search

29 August 2000

Date of mailing of the international search report

05/09/2000.

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Papastefanou, E

INTERNATIONAL SEARCH REPORT

Int. Application No
PCT/GB 00/01718

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 805 034 A (MARKEM CORP) 5 November 1997 (1997-11-05) column 3, line 53 -column 5, line 42 figure 1	11,13
A	---	1,10, 14-16
A	EP 0 660 092 A (CANON KK) 28 June 1995 (1995-06-28) column 2, line 16 -column 3, line 30 figure 2 -----	1,2,7

INTERNATIONAL SEARCH REPORT

Int. Application No
PCT/GB 00/01718

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0838339	A	29-04-1998	JP 10128994 A	19-05-1998
US 5880748	A	09-03-1999	NONE	
EP 0805034	A	05-11-1997	US 5920332 A	06-07-1999
			GB 2312649 A, B	05-11-1997
			JP 10058710 A	03-03-1998
EP 0660092	A	28-06-1995	JP 63257645 A	25-10-1988
			JP 2528655 B	28-08-1996
			JP 63257646 A	25-10-1988
			DE 3855448 D	05-09-1996
			DE 3855448 T	02-01-1997
			EP 0287098 A	19-10-1988
			US 5729256 A	17-03-1998
			US 4977413 A	11-12-1990

Form PCT/ISA/210 (patent family annex) (July 1992)